## NSN 5930-00-253-2347

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-253-2347

Thread Length:

0.375 inches single mounting facility

**Overall Length:** 

2.000 inches

First Flat Length:

0.344 inches single actuator

Flat Height:

0.219 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.875 inches single actuator

**Individual Section Quantity:** 

1

**Knob Manufacturer Code:** 

44655

**Knob Manufacturer Part Number:** 

5116a

**Nonturn Device Type:** 

Tab at 6: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

11 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Actuator knob

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Shaft Flat/slot Angular Location:** 

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:** 

11 single actuator

Shaft Type:

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

## NSN 5930-00-253-2347

Rotary Switch - Page 2 of 2



## **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Detent Rotational Torque Range:** +1.500/+3.800 inch-pounds single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 15.0 amperes resistive load ac at sea level **Style Designator:** Tap, circular, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A052b0