# NSN 5930-00-253-2868

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-253-2868

## **Thread Class:**

2a single mounting facility

### Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

1.688 inches

#### **Overall Height:**

1.875 inches

#### **Overall Width:**

1.563 inches

#### First Flat Length:

0.406 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.500 inches single actuator

### Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

3 single section rear

#### **Throw Quantity:**

1 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Shaft Flat/slot Angular Location:

0.0 degrees from contact position 1 single actuator

## Switch Actuator Indexing Position Quantity:

2 single actuator

### Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section rear

# NSN 5930-00-253-2868

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

## Style Designator:

Circular wafer, bushing mount

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0