NSN 5930-00-253-4257

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-253-4257

Body Style:
Hole mounted
Overall Length:
3.700 inches
Overall Width:
1.570 inches
Actuator Style:
Round
Actuator Diameter:
0.360 inches
Actuator Free Position Height:
1.600 inches
Housing Length:
3.700 inches
Housing Width:
1.570 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.310 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.190 inches
Maximum Voltage Rating In Volts:
480.0 ac and 550.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
32.0 ounces
Switch Actuating Force:
144.0 ounces
Actuator Movement:
Between 0.109 pretravel inches and 0.250 overtravel inches and 0.040 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
0.100 milliamperes resistive dc and 10.000 amperes resistive ac
Test Data Document:
11243-3200529-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 screw
Shelf Life:

N/a

NSN 5930-00-253-4257

Sensitive Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A053a0