NSN 5930-00-253-8785

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-253-8785

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
1.047 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
1.609 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.297 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.156 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
8.5 ounces
Actuator Movement:
Between 0.172 pretravel inches and 0.156 overtravel inches and 0.025 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
25.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

NSN 5930-00-253-8785

Sensitive Switch - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0