

View Online at <https://aerobasegroup.com/nsn/5930-00-253-8785>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.938 inches

**Body Width:**

0.688 inches

**Body Height:**

1.047 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Length:**

1.609 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

1.297 inches

**Actuator Roller Diameter:**

0.375 inches

**Actuator Roller Width:**

0.156 inches

**Maximum Voltage Rating In Volts:**

460.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

8.5 ounces

**Actuator Movement:**

Between 0.172 pretravel inches and 0.156 overtravel inches and 0.025 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0