

View Online at <https://aerobasegroup.com/nsn/5930-00-253-8803>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Switch Actuator Quantity:

1

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Height:

0.109 inches

Actuator Width:

0.165 inches

Actuator Free Position Height:

0.625 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.046 pretravel inches and 0.031 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc and 6.000 amperes motor dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes motor ac

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0