NSN 5930-00-254-0332

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-254-0332

| Hazardous Locations/environmental Protection: |
|---|
| Dustproof |
| Overall Length: |
| 0.828 inches |
| Overall Height: |
| 0.312 inches |
| Body Diameter: |
| 0.359 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 0.438 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 0.719 inches |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Mounting Method: |
| Bracket |
| Features Provided: |
| Automatic reset |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Four position rectangular |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 750.0 milliamperes resistive load second voltage |
| Contact Adjustability: |
| Actuation point not adjustable |
| Contact Stimulus Rating: |
| 150.80 actuation point degrees fahrenheit and 143.60 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 12.5 dc at sea level third voltage |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |
| Cylindrical w/port |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5930-00-254-0332

Thermostatic Switch - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A048b0