

View Online at <https://aerobasegroup.com/nsn/5930-00-254-0334>

**Overall Length:**

0.812 inches

**Overall Height:**

0.312 inches

**Overall Width:**

0.828 inches

**Body Length:**

0.300 inches

**Body Width:**

0.719 inches

**Unthreaded Mounting Hole Diameter:**

0.104 inches

**Distance Between Mounting Facility Centers:**

0.625 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

2.5 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

-20.00/+200.00 actuation point degrees fahrenheit and -20.00/+200.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

80.00 actuation point degrees celsius and 75.00 deactuation point degrees celsius and 5.00 differential point degrees celsius

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0