NSN 5930-00-254-0334

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-254-0334

Overall Length:
0.812 inches
Overall Height:
0.312 inches
Overall Width:
0.828 inches
Body Length:
0.300 inches
Body Width:
0.719 inches
Unthreaded Mounting Hole Diameter:
0.104 inches
Distance Between Mounting Facility Centers:
0.625 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
2.5 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
-20.00/+200.00 actuation point degrees fahrenheit and -20.00/+200.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:
80.00 actuation point degrees celsius and 75.00 deactuation point degrees celsius and 5.00 differential point degrees celsius
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:

Gas or liquid

NSN 5930-00-254-0334

Thermostatic Switch - Page 2 of 2



Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0