## NSN 5930-00-254-1000

Rotary Switch - Page 1 of 2

0.375 inches single mounting facility

**Thread Class:** 

Thread Length:

**Overall Length:** 

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-254-1000

4.125 inches **Overall Height:** 1.875 inches **Overall Width:** 1.625 inches First Flat Length: 0.313 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.813 inches single actuator **Individual Section Quantity:** 2 **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 4 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round, v flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks each section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-254-1000

Rotary Switch - Page 2 of 2



Contact Load Current Rating
-----------------------------

500.0 milliamperes resistive load ac at sea level

**Precious Material And Location:** 

Contacts and rotor blade surfaces silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0