NSN 5930-00-254-7088

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-254-7088

view Online at https://aerobasegroup.com/nsn/5930-00-254-7088
Thread Class:
3b single pressure connection
Thread Length:
0.500 inches single pressure connection
Overall Length:
3.000 inches
Overall Height:
3.625 inches
Overall Width:
1.938 inches
Body Height:
2.500 inches
Pressure Switch Type:
Differential
Width Across Flats:
0.625 inches
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Nonpile-up Contact Arrangement:
2 pole, single throw, normally closed, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
10.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+20.00/+25.00 actuation point pounds per square inch gage and +30.00/+60.00 deactuation point pounds per square inch gage
Contact Adjustment Type:
Internal actuation point shaft
Contact Voltage Rating In Volts:
120.0 ac at sea level single voltage
Pressure Connector Type:

Plain, threaded internal single connection **Frequency In Hertz:**

60.0 single voltage

NSN 5930-00-254-7088

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0