### NSN 5930-00-254-9139

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-254-9139

**Thread Class:** 

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Width Between Flats:

0.187 inches single actuator

**Overall Length:** 

2.281 inches

**Overall Height:** 

1.875 inches

**Overall Width:** 

1.609 inches

First Flat Length:

0.281 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.969 inches single actuator

**Individual Section Quantity:** 

1

### **Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:** 

2 single section rear

**Throw Quantity:** 

4 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

#### **Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:** 

Round, parallel flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

# NSN 5930-00-254-9139

Rotary Switch - Page 2 of 2



# **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Contacts and rotor blade surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0