

View Online at <https://aerobasegroup.com/nsn/5930-00-255-5898>

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

Between 6.546 inches and 6.578 inches

**First Flat Length:**

0.484 inches single actuator and 0.516 inches single actuator

**Flat Height:**

0.214 inches single actuator and 0.224 inches single actuator

**Shaft Diameter:**

0.243 inches single actuator and 0.253 inches single actuator

**Shaft Length:**

5.046 inches single actuator and 5.078 inches single actuator

**Individual Section Quantity:**

2

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 2nd section front

**Throw Quantity:**

5 2nd section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 lowest ac voltage rating at sea level

**Shaft Flat/slot Angular Location:**

22.5 degrees from contact position 1 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0