

View Online at <https://aerobasegroup.com/nsn/5930-00-255-9351>

**Thread Class:**

3a single pressure connection

**Thread Length:**

0.292 inches single pressure connection

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

2.750 inches

**Outside Diameter:**

0.438 inches single connection

**Body Length:**

1.688 inches

**Overall Diameter:**

0.680 inches

**Pressure Switch Type:**

Absolute

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 71.0 degrees celsius

**Mounting Method:**

Clamp

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

120.00 pounds per square inch

**Thread Size:**

0.4375 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

2.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

22.50 actuation point pounds per square inch absolute and 15.00 deactuation point pounds per square inch absolute

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0