

View Online at <https://aerobasegroup.com/nsn/5930-00-256-4552>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

10.832 inches

Overall Height:

2.312 inches

Overall Width:

1.968 inches

Shaft Diameter:

0.375 inches 1st actuator

Shaft Length:

2.859 inches 3rd actuator

Nonturn Device Radius:

0.531 inches at 10: 30 o'clock

Individual Section Quantity:

8

Nonturn Device Type:

Tab at 10: 30 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 8th section rear

Throw Quantity:

6 7th section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.625 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 7th section

Switch Actuator Indexing Position Quantity:

24 all actuators

Shaft Type:

Round, hollowed 2nd actuator

Terminal Type:

Clip

Contact Switching Action:

Makes before breaks 7th section rear

Switch Actuator Positioning Increment:

15.0 degrees all actuators

Detent Rotational Torque Range:

+5.000/+20.000 inch-ounces 3rd actuator

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Clips and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0