

View Online at <https://aerobasegroup.com/nsn/5930-00-256-8935>

Thread Class:

2a single mounting facility

Thread Length:

0.410 inches single mounting facility and 0.450 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.650 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.209 inches single actuator and 0.219 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.890 inches single actuator and 0.970 inches single actuator

Overall Diameter:

1.125 inches

Individual Section Quantity:

3

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

+0.0/+80.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 each section front

Throw Quantity:

10 2nd section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Special Features:

Provides rf interference panel shielding

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-s-3786/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0