NSN 5930-00-256-8982

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-256-8982

| Body Style: |
|---|
| Hole mounted |
| Overall Length: |
| 1.360 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.125 inches |
| Overall Height: |
| 0.701 inches |
| Overall Width: |
| 0.550 inches |
| Body Length: |
| 0.880 inches |
| Body Width: |
| 0.550 inches |
| Body Height: |
| 0.310 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Length: |
| 0.217 inches |
| Actuator Height: |
| 0.031 inches |
| Actuator Width: |
| 0.224 inches |
| Actuator Position-action Relationship: |
| Left position maintained and right position maintained |
| Maximum Voltage Rating In Volts: |
| 230.0 ac |
| Mounting Method: |
| Bracket and unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 500.000 milliamperes resistive dc and 6.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5930-00-256-8982

Slide Switch - Page 2 of 2



Fiig:

A053a0