

View Online at <https://aerobasegroup.com/nsn/5930-00-256-9168>

**Thread Length:**

0.375 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Sand proof

**Overall Length:**

2.586 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**First Flat Length:**

0.218 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Individual Section Quantity:**

3

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

8 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

0.5 amperes resistive load dc at sea level and 0.2 amperes inductive load dc at sea level

**Special Features:**

Nonturn device type flatted bushing

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0