

View Online at <https://aerobasegroup.com/nsn/5930-00-256-9168>

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Sand proof

Overall Length:

2.586 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

First Flat Length:

0.218 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Individual Section Quantity:

3

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

8 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

0.5 amperes resistive load dc at sea level and 0.2 amperes inductive load dc at sea level

Special Features:

Nonturn device type flatted bushing

Style Designator:

Tap, square frame

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0