## NSN 5930-00-257-2902

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-257-2902

| view Online at https://derobasegroup.com/nsi//0550-50-257-2502                     |
|--|
| Body Style:  |
| Hole mounted   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:           |
| 0.532 inches   |
| Body Length:   |
| 4.500 inches   |
| Body Width:  |
| 0.938 inches   |
| Body Height:   |
| 1.188 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Height:          |
| 0.812 inches   |
| Actuator Style:  |
| Round  |
| Actuator Height:   |
| 1.234 inches   |
| Actuator Position-action Relationship:   |
| Up position maintained and down position maintained and center position maintained |
| Actuator Position-locking Relationship:  |
| Up position locked in and down position locked in and center position locked in    |
| Actuator Color:  |
| Black single actuator  |
| Maximum Voltage Rating In Volts:   |
| 110.0 ac   |
| Inclosure Type:  |
| Uninclosed   |
| Thready Qty Per Inch (tpi):  |
| 40   |
| Pile-up Contact Form Arrangement:  |
| 4c single position   |
| Thread Size:   |
| 0.112 inches   |
| Contact Load Current Rating At Maximum Rated Voltage:                              |
| 3.000 amperes resistive ac   |
| Special Features:  |
| Nickel plated body   |
| Thread Series Designator:  |
| Unc  |
| Terminal Type And Quantity:  |
| 12 tab, solder lug   |
| Shelf Life:  |

N/a

## NSN 5930-00-257-2902

Lever Switch - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A053a0