NSN 5930-00-257-3006

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-257-3006

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
1.210 inches
Overall Height:
3.320 inches
Overall Width:
Between 0.950 inches and 0.970 inches
Body Length:
1.200 inches
Body Width:
Between 0.950 inches and 0.970 inches
Body Height:
3.110 inches
Case Material:
Metal
Actuator Length:
Between 1.020 inches and 1.050 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.164 inches and 0.210 inches
Actuator Width:
Between 0.720 inches and 0.750 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
White single actuator and white single actuator
Actuator Inscription:
Simulated on/simulated off single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit

NSN 5930-00-257-3006

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0