

View Online at <https://aerobasegroup.com/nsn/5930-00-257-3255>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

3.656 inches

Overall Height:

1.875 inches

Overall Width:

1.625 inches

First Flat Length:

0.438 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.750 inches single actuator

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

135.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.5 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0