

View Online at <https://aerobasegroup.com/nsn/5930-00-257-3257>

Thread Class:

2a single mounting facility

Thread Length:

0.245 inches single mounting facility and 0.255 inches single mounting facility

Overall Length:

Between 2.964 inches and 2.974 inches

Shaft Diameter:

0.245 inches single actuator and 0.255 inches single actuator

Shaft Length:

0.589 inches single actuator and 0.599 inches single actuator

Overall Diameter:

Between 1.933 inches and 1.943 inches

Nonturn Device Radius:

0.531 inches at 2: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 2: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+30.000/+40.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0