

View Online at <https://aerobasegroup.com/nsn/5930-00-257-8988>

Thread Class:

3a single pressure connection

Thread Length:

0.550 inches single pressure connection

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

2.750 inches

Body Length:

1.403 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Tempurature Rating:

Between -34.0 degrees celsius and 74.0 degrees celsius

Mounting Method:

Clamp

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1500.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

45.00 actuation point pounds per square inch gage and 15.00 deactuation point pounds per square inch gage and 30.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0