NSN 5930-00-257-8988

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-257-8988 **Thread Class:** 3a single pressure connection **Thread Length:** 0.550 inches single pressure connection **Hazardous Locations/environmental Protection:** Weatherproof **Overall Length:** 2.750 inches **Body Length:** 1.403 inches **Pressure Switch Type:** Gage Width Across Flats: 0.750 inches **Operating Tempurature Rating:** Between -34.0 degrees celsius and 74.0 degrees celsius **Mounting Method:** Clamp **Features Provided:** Electrical box connector Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Proof Pressure:** 1500.00 pounds per square inch **Thread Size:** 0.438 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 2.0 amperes resistive load single voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 45.00 actuation point pounds per square inch gage and 15.00 deactuation point pounds per square inch gage and 30.00 differential point pounds per square inch gage **Contact Voltage Rating In Volts:**

contact ronage naming in rone.

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

NSN 5930-00-257-8988

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0