

View Online at <https://aerobasegroup.com/nsn/5930-00-258-0103>

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

0.984 inches

Body Width:

0.840 inches

Body Height:

1.074 inches

Actuator Style:

Round

Actuator Diameter:

0.428 inches

Actuator Height:

1.560 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked in

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Oship ohio class ss (trident), los angeles class ssn(688), sturgeon class ssn(637) emory s. Land class as, submarine communications and antenna systems, communications systems an/wrr-7, aircraft hercules c-130f, e-6 tacamo

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, three positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 10.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0