## NSN 5930-00-258-1894

Lever Switch - Page 1 of 2

**Thread Class:** 

2b



View Online at https://aerobasegroup.com/nsn/5930-00-258-1894

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.375 inches
Overall Height:
1.382 inches
Overall Width:
0.750 inches
Body Length:
0.375 inches
Body Width:
0.750 inches
Body Height:
1.132 inches
Actuator Length:
1.281 inches
Actuator Style:
Rectangular
Actuator Position-action Relationship:
Up position maintained and down position maintained
Maximum Voltage Rating In Volts:
30.0 dc
30.0 dC
Inclosure Type:
Inclosure Type:
Inclosure Type: Uninclosed
Inclosure Type: Uninclosed Mounting Method:
Inclosure Type: Uninclosed Mounting Method: Bracket and threaded hole
Inclosure Type: Uninclosed  Mounting Method: Bracket and threaded hole Thready Qty Per Inch (tpi):
Inclosure Type: Uninclosed Mounting Method: Bracket and threaded hole Thready Qty Per Inch (tpi): 40
Inclosure Type: Uninclosed  Mounting Method: Bracket and threaded hole  Thready Qty Per Inch (tpi): 40  Pile-up Contact Form Arrangement:
Inclosure Type: Uninclosed Mounting Method: Bracket and threaded hole Thready Qty Per Inch (tpi): 40 Pile-up Contact Form Arrangement: 2c single position
Inclosure Type: Uninclosed  Mounting Method: Bracket and threaded hole  Thready Qty Per Inch (tpi): 40  Pile-up Contact Form Arrangement: 2c single position  Thread Size:
Inclosure Type: Uninclosed  Mounting Method: Bracket and threaded hole Thready Qty Per Inch (tpi): 40 Pile-up Contact Form Arrangement: 2c single position Thread Size: 0.125 inches
Inclosure Type: Uninclosed  Mounting Method: Bracket and threaded hole  Thready Qty Per Inch (tpi): 40  Pile-up Contact Form Arrangement: 2c single position  Thread Size: 0.125 inches  Contact Load Current Rating At Maximum Rated Voltage:
Inclosure Type: Uninclosed  Mounting Method: Bracket and threaded hole Thready Qty Per Inch (tpi): 40 Pile-up Contact Form Arrangement: 2c single position Thread Size: 0.125 inches Contact Load Current Rating At Maximum Rated Voltage: 100.000 milliamperes resistive dc
Inclosure Type: Uninclosed Mounting Method: Bracket and threaded hole Thready Qty Per Inch (tpi): 40 Pile-up Contact Form Arrangement: 2c single position Thread Size: 0.125 inches Contact Load Current Rating At Maximum Rated Voltage: 100.000 milliamperes resistive dc Special Features:
Inclosure Type: Uninclosed Mounting Method: Bracket and threaded hole Thready Qty Per Inch (tpi): 40 Pile-up Contact Form Arrangement: 2c single position Thread Size: 0.125 inches Contact Load Current Rating At Maximum Rated Voltage: 100.000 milliamperes resistive dc Special Features: Thd stud mtg; Iver has 909 bend in end
Inclosure Type: Uninclosed  Mounting Method: Bracket and threaded hole Thready Qty Per Inch (tpi): 40 Pile-up Contact Form Arrangement: 2c single position Thread Size: 0.125 inches Contact Load Current Rating At Maximum Rated Voltage: 100.000 milliamperes resistive dc Special Features: Thd stud mtg; Iver has 909 bend in end Thread Series Designator:

## NSN 5930-00-258-1894

Lever Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0