

View Online at <https://aerobasegroup.com/nsn/5930-00-258-4255>

Thread Length:

0.673 inches single mounting facility

First Flat Length:

0.665 inches single actuator

Flat Height:

0.281 inches single actuator

Shaft Diameter:

0.373 inches single actuator

Shaft Length:

2.312 inches single actuator

Individual Section Quantity:

2

End Application:

Nimitz class cvn; forrestal class cv; moored training ship; cvn 68 class reactor fill auxiliary system; spruance class dd (963); conveyers fleet vertical package; arleigh burke class ddg; los angeles class ssn (688); sturgeon class ssn (637); ticonderoga class cg (47)

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Switch Actuator Indexing Position Quantity:

16 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Special Features:

Bushing 0.620 in. Dia. With 24 thd per in.; weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0