NSN 5930-00-258-4623

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-4623 **Body Style:** Hole mount **Overall Length:** 1.875 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.312 inches **Overall Height:** 2.203 inches **Overall Width:** 0.812 inches **Body Length:** 1.875 inches **Body Width:** 0.812 inches **Body Height:** 1.422 inches **Actuator Diameter:** 0.562 inches **Actuator Height:** 0.781 inches **Maximum Voltage Rating In Volts:** 440.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes inductive dc and 4.000 amperes lamp dc and 20.000 amperes motor dc and 25.000 amperes resistive dc and 2.000 amperes inductive ac and 3.200 amperes motor ac and 4.200 amperes resistive ac **Thread Series Designator: Terminal Type And Quantity:** 2 screw Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5930-00-258-4623

Push Switch - Page 2 of 2



Fiig:

A053a0