NSN 5930-00-258-5249

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5249

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof and moisture proof
Overall Length:
4.000 inches
Overall Height:
3.268 inches
Overall Width:
1.300 inches
Actuator Style:
Round
Actuator Diameter:
0.330 inches
Actuator Height:
1.014 inches
Actuator Free Position Height:
2.188 inches
Housing Height:
2.160 inches
Housing Length:
4.000 inches
Housing Width:
1.300 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.625 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.250 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
8.0 ounces
Switch Actuating Force:

40.0 ounces

NSN 5930-00-258-5249

Sensitive Switch - Page 2 of 2



Actuator	Movement:
----------	-----------

Between 0.094 pretravel inches and 0.219 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0