

View Online at <https://aerobasegroup.com/nsn/5930-00-258-5249>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Length:

4.000 inches

Overall Height:

3.268 inches

Overall Width:

1.300 inches

Actuator Style:

Round

Actuator Diameter:

0.330 inches

Actuator Height:

1.014 inches

Actuator Free Position Height:

2.188 inches

Housing Height:

2.160 inches

Housing Length:

4.000 inches

Housing Width:

1.300 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.625 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.250 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

40.0 ounces

Actuator Movement:

Between 0.094 pretravel inches and 0.219 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0