

View Online at <https://aerobasegroup.com/nsn/5930-00-258-5252>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and oiltight

Overall Length:

4.062 inches

Overall Height:

2.718 inches

Overall Width:

1.000 inches

Actuator Length:

1.562 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

2.438 inches

Actuator Roller Diameter:

0.375 inches

Housing Height:

1.656 inches

Housing Length:

2.750 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

0.343 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.250 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

48.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.469 overtravel inches and 0.014 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Left hand design

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0