## NSN 5930-00-258-5252

Sensitive Switch - Page 1 of 2

48.0 ounces



View Online at https://aerobasegroup.com/nsn/5930-00-258-5252

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof and oiltight
Overall Length:
4.062 inches
Overall Height:
2.718 inches
Overall Width:
1.000 inches
Actuator Length:
1.562 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
2.438 inches
Actuator Roller Diameter:
0.375 inches
Housing Height:
1.656 inches
Housing Length:
2.750 inches
Housing Width:
1.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
0.343 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.250 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:

## NSN 5930-00-258-5252

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	Mov	ıρm	Δn	+
~	υιu	awı	IVIO	ven		ш.

Between 0.078 pretravel inches and 0.469 overtravel inches and 0.014 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Special Features:** 

Left hand design

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0