

View Online at <https://aerobasegroup.com/nsn/5930-00-258-5257>

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.156 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.156 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

19.0 ounces

Actuator Movement:

Between 0.109 pretravel inches and 0.074 overtravel inches and 0.001 differential inches and 0.011 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0