

View Online at <https://aerobasegroup.com/nsn/5930-00-258-5280>

**Body Style:**

Hole mounted

**Actuator Length:**

1.570 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.906 inches

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.312 inches

**Housing Height:**

1.750 inches

**Housing Length:**

3.020 inches

**Housing Width:**

1.000 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

0.917 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

18.0 ounces

**Actuator Movement:**

Between 0.188 pretravel inches and 0.219 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0