## NSN 5930-00-258-5280

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5280

Body Style:
Hole mounted
Actuator Length:
1.570 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.906 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.312 inches
Housing Height:
1.750 inches
Housing Length:
3.020 inches
Housing Width:
1.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
0.917 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
6.0 ounces
Switch Actuating Force:
18.0 ounces
Actuator Movement:
Between 0.188 pretravel inches and 0.219 overtravel inches and 0.006 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Unc

**Thread Series Designator:** 

## NSN 5930-00-258-5280

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0