NSN 5930-00-258-5290

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5290

Body Style:
Hole mounted
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.005 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.950 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Height:
0.055 inches
Actuator Free Position Height:
0.646 inches
Maximum Voltage Rating In Volts:
600.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
20.0 ounces
Actuator Movement:
Between 0.020 pretravel inches and 0.005 overtravel inches and 0.003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:
300.000 milliamperes resistive dc and 50.000 milliamperes inductive dc and 2.000 amperes resistive ac and 0.500 amperes lamp ac and

300.000 milliamperes resistive dc and 50.000 milliamperes inductive dc and 2.000 amperes resistive ac and 0.500 amperes lamp ac and 2.000 amperes motor ac

NSN 5930-00-258-5290

Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0