NSN 5930-00-258-5290

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5290

| Body Style: |
|--|
| Hole mounted |
| Overall Length: |
| 1.940 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Overall Height: |
| 1.005 inches |
| Overall Width: |
| 0.687 inches |
| Body Length: |
| 1.940 inches |
| Body Width: |
| 0.687 inches |
| Body Height: |
| 0.950 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.094 inches |
| Actuator Height: |
| 0.055 inches |
| Actuator Free Position Height: |
| 0.646 inches |
| Maximum Voltage Rating In Volts: |
| 600.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| 20.0 ounces |
| Actuator Movement: |
| Between 0.020 pretravel inches and 0.005 overtravel inches and 0.003 differential inches |

Contact Load Current Rating At Maximum Rated Voltage:
300.000 milliamperes resistive dc and 50.000 milliamperes inductive dc and 2.000 amperes resistive ac and 0.500 amperes lamp ac and

300.000 milliamperes resistive dc and 50.000 milliamperes inductive dc and 2.000 amperes resistive ac and 0.500 amperes lamp ac and 2.000 amperes motor ac

NSN 5930-00-258-5290

Sensitive Switch - Page 2 of 2



| Precious Material And Location: |
|---------------------------------|
| Contacts silver |
| Terminal Type And Quantity: |
| 3 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0