## NSN 5930-00-258-5309

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted

Dustproof

Overall Length: 1.938 inches



View Online at https://aerobasegroup.com/nsn/5930-00-258-5309

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Width:
0.688 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
1.047 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.156 inches
Actuator Adapter Style:
Roller arm
Maximum Voltage Rating In Volts:
125.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:
1.0 ounces
Actuator Movement:
Between 0.156 pretravel inches and 0.093 overtravel inches and 0.020 differential inches

## NSN 5930-00-258-5309

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0