

View Online at <https://aerobasegroup.com/nsn/5930-00-258-5311>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.500 inches

Overall Width:

0.687 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

0.954 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.158 inches

Actuator Height:

0.232 inches

Actuator Free Position Height:

1.140 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

1.5 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.050 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes motor dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 5.000 amperes motor ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 screw

Specification Data:

81349-mil-s-8805/61 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0