

View Online at <https://aerobasegroup.com/nsn/5930-00-258-5311>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

1.940 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Overall Height:**

1.500 inches

**Overall Width:**

0.687 inches

**Body Length:**

1.940 inches

**Body Width:**

0.687 inches

**Body Height:**

0.954 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.158 inches

**Actuator Height:**

0.232 inches

**Actuator Free Position Height:**

1.140 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Actuating Force:**

1.5 ounces

**Actuator Movement:**

Between 0.030 pretravel inches and 0.050 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes motor dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 5.000 amperes motor ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 screw

**Specification Data:**

81349-mil-s-8805/61 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0