NSN 5930-00-258-5339

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5339

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.250 inches
Overall Height:
4.000 inches
Overall Width:
5.875 inches
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.375 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
13379
Knob Manufacturer Part Number:
14-11
Longest Horizontal Distance Between Mounting Centers:
5.000 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Base single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and cam actuated
Contact Voltage Rating In Volts:
440.0 ac at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Cam Actuated Switch Contact Arrangement:
1 pole, double throw, both positions maintained single switch single section in-line
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:

Breaks before makes single section in-line

NSN 5930-00-258-5339

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0