## NSN 5930-00-258-5339

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5339

| Hazardous Locations/environmental Protection:  |
|--|
| Watertight   |
| Overall Length:  |
| 5.250 inches   |
| Overall Height:  |
| 4.000 inches   |
| Overall Width:   |
| 5.875 inches   |
| Shaft Diameter:  |
| 0.375 inches single actuator   |
| Shaft Length:  |
| 1.750 inches single actuator   |
| Unthreaded Mounting Hole Diameter:   |
| 0.375 inches single mounting facility  |
| Individual Section Quantity:   |
| 1  |
| Knob Manufacturer Code:  |
| 13379  |
| Knob Manufacturer Part Number:   |
| 14-11  |
| Longest Horizontal Distance Between Mounting Centers:                                |
| 5.000 inches single mounting facility  |
| Switch Contact Basic Design:   |
| Nonpile-up nonsymmetrical  |
| Mounting Method:   |
| Base single mounting facility and unthreaded hole single mounting facility           |
| Features Provided:   |
| Actuator knob and cam actuated   |
| Contact Voltage Rating In Volts:   |
| 440.0 ac at sea level  |
| Mounting Facility Pattern:   |
| Two position in-line single mounting facility  |
| Cam Actuated Switch Contact Arrangement:   |
| 1 pole, double throw, both positions maintained single switch single section in-line |
| Switch Actuator Indexing Position Quantity:  |
| 2 single actuator  |
| Shaft Type:  |
| Round single actuator  |
| Terminal Type:   |
| Tab w/screw  |
| Contact Switching Action:  |

Breaks before makes single section in-line

## NSN 5930-00-258-5339

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load ac at sea level

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0