## NSN 5930-00-258-5344

**Hazardous Locations/environmental Protection:** 

Rotary Switch - Page 1 of 2

Dustproof

Overall Height: 2.500 inches Overall Width: 2.500 inches

First Flat Length:

Flat Height:

**Shaft Diameter:** 

**Shaft Length:** 

0.500 inches single actuator

0.216 inches single actuator



View Online at https://aerobasegroup.com/nsn/5930-00-258-5344

0.248 inches single actuator and 0.250 inches single actuator

1.188 inches single actuator
Unthreaded Mounting Hole Diameter:
0.173 inches single mounting facility
Individual Section Quantity:
1
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section in-line
Throw Quantity:
1 single section in-line
Mounting Facility Circle Radius:
1.106 inches single mounting facility
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Metallic inclosure
Contact Voltage Rating In Volts:
6.0 dc at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section in-line

## NSN 5930-00-258-5344

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

10.0 amperes resistive load dc at sea level

**Precious Material And Location:** 

Contacts silver

**Precious Material:** 

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0