## NSN 5930-00-258-5363

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5363

Width Between Flats:
0.250 inches single actuator
Hazardous Locations/environmental Protection:
Explosion proof
Overall Height:
7.000 inches
Overall Width:
3.625 inches
First Flat Length:
0.469 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9s4923l7
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
1 each section front
Mounting Facility Circle Radius:
1.875 inches single mounting facility
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
120.0 ac at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator

## NSN 5930-00-258-5363

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load ac at sea level

**Specification Or Standard:** 

A-p type

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0