NSN 5930-00-258-5399

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5399

0	Law with a
Overall	Length:

3.000 inches

Overall Height:

3.000 inches

Overall Width:

1.875 inches

Distance Between Mounting Facility Centers:

1.188 inches

Capillary Tube Length:

72.000 inches

Bulb Length:

10.750 inches

Bulb Diameter:

0.375 inches

Tempurature Sensing Element Type:

Capillary tube-bulb

Operating Tempurature Rating:

120.0 degrees fahrenheit

Mounting Method:

Bracket and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

200.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+20.00/+105.00 actuation point degrees fahrenheit and +20.00/+105.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

NSN 5930-00-258-5399

Thermostatic Switch - Page 2 of 2



Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0