

View Online at <https://aerobasegroup.com/nsn/5930-00-258-5573>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Watertight and dustproof

Overall Length:

5.188 inches

Overall Height:

5.593 inches

Overall Width:

2.812 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

-20.00/+80.00 actuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0