## NSN 5930-00-258-5604

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5604

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
2.500 inches
Overall Height:
3.657 inches
Overall Width:
1.218 inches
Case Material:
Metal
Actuator Length:
1.562 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.094 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.125 inches
Housing Height:
1.250 inches
Housing Length:
2.500 inches
Housing Width:
1.218 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.563 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.875 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit

144.0 ounces

**Switch Actuating Force:** 

## NSN 5930-00-258-5604

Sensitive Switch - Page 2 of 2



Actuator	Movement:
----------	-----------

Between 4.0 pretravel degrees and 8.0 overtravel degrees and 1.5 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:** 

15.000 amperes resistive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:** 

1 connector, receptacle

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0