Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5659

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
19.875 inches
Overall Height:
2.812 inches
Overall Width:
2.812 inches
Shaft Length:
1.688 inches single actuator
Unthreaded Mounting Hole Diameter:
0.531 inches single mounting facility
Individual Section Quantity:
25
Knob Manufacturer Code:
10001
Knob Manufacturer Part Number:
9-s-5564-l piece 20
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Facility Circle Radius:
6.875 inches single mounting facility
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
30.0 dc at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:
0.375 inches single actuator
Terminal Type:
Screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator

NSN 5930-00-258-5659

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0