## NSN 5930-00-258-5667

Push Switch - Page 1 of 2

3 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5930-00-258-5667

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.313 inches
Overall Height:
0.875 inches
Overall Width:
0.875 inches
Body Diameter:
0.562 inches
Bushing Length:
0.312 inches
Body Length:
0.422 inches
Case Material:
Metal
Actuator Diameter:
0.375 inches
Actuator Height:
0.188 inches
Maximum Voltage Rating In Volts:
120.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 10.000 amperes resistive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:

## NSN 5930-00-258-5667

Push Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0